


## DS-2AE4023(N)I-D 700TVL IR Analog PTZ Dome Camera



Hikvision DS-2AE4023(N)I-D IR Analog PTZ Dome Cameras are able to capture high quality images in low light environment with its black anti-reflective glass. The black anti-reflective glass increase the luminousness which can reach up to 100m IR distance.

Embedded with 1/3" CCD chip makes WDR possible. With the 23X optical zoom Day/Night lens, the camera offers more details over expansive areas.

### Key Features

- 1/3" Progressive Scan CCD
- 700TVL
- 23X Optical Zoom
- DWDR
- Support IP66
- Up to 100m IR distance
- 3D intelligent positioning function



# DS-2AE4023(N)I-D 700TVL IR Analog PTZ Dome Camera



## Function Description

### **System function:**

- 1/3" high performance CCD, up to 700TVL
- $\pm 0.1^\circ$  Preset Accuracy
- Self-adaptive to HIKVISION, Pelco-P/D protocol
- 3D intelligent positioning function
- Power-off memory function: restore PTZ & Lens status after reboot
- Built-in temperature sensor, with display of internal temperature
- Lightning protection, surge protection and voltage transient protection
- IP66 standard (outdoor dome)
- RS-485 communication diagnosis
- Scheduled PTZ movement

### **Camera function:**

- Auto focus, auto white balance, backlight compensation and auto/manual day & night switch
- Privacy masks programmable
- 3D DNR, digital zoom
- DWDR, EIS

### **PTZ function:**

- $360^\circ$  endless pan range and  $-15^\circ$  -  $-90^\circ$  tilt range
- $80^\circ$  /s Pan Preset Speed and  $80^\circ$  /s Tilt Preset Speed
- $0.1^\circ$  -  $80^\circ$  /s Manual Pan Speed and  $0.1^\circ$  -  $80^\circ$  /s Manual Tilt Speed
- 256 presets programmable; preset image freezing capability

- 8 patrols, up to 32 presets per patrol
- 4 patterns, with the total recording time not less than 10 minutes
- Proportional zoom function
- Park action: auto call up of PTZ movement, after a defined time of inactivity

# DS-2AE4023(N)I-D 700TVL IR Analog PTZ Dome Camera




<b>Model</b>	<b>DS-2AE4023I-D/DS-2AE4023NI-D</b>
<b>Camera Module</b>	
Image Sensor	1/3" CCD
Min. Illumination	Color: 0.02Lux@( F1.6,AGC ON); B/W: 0.002Lux@( F1.6,AGC ON), 0 Lux with IR
Horizontal Resolution	700TVL
Focal Length	4-92.0mm, 23x
Digital Zoom	16X
Zoom Speed	Approx.3s(Optical Wide~Tele)
Angle of View	49-2.2 degree(Wide~Tele)
Min. Working Distance	10~1,000mm(Wide~Tele)
Aperture Range	F1.6-F3.7
Focus Mode	Auto / Semiautomatic / Manual
DWDR	Support
S / N Ratio	≥ 50dB
Shutter Time	1-1/10,000s
AGC	Auto / Manual
White Balance	Auto / Manual / ATW / Indoor / Outdoor
Day & Night	IR Cut Filter
Privacy Mask	8 privacy masks programmable; a maximum of 8 zones can be masked simultaneously on the same video screen
Enhancement	3D DNR, BLC, EIS
<b>Pan and Tilt</b>	
Range	Pan:360° endless; Tilt: -15°~90°(Auto Flip)
Speed	Pan Manual Speed: 0.1°~80°/s, Pan Preset Speed: 80°/s Tilt Manual Speed: 0.1°~80°/s, Tilt Preset Speed: 80°/s
Number of Preset	256
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the total recording time not less than 10 minutes
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Panorama scan
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Panorama scan
RS-485 communication diagnosis	Support
<b>Infrared</b>	
IR Distance	Up to 100m
IR Intensity	Automatically adjusted, depending on the zoom ratio
<b>Input/ Output</b>	
CVBS Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
RS-485 Interface	Half-duplex mode Self-adaptive HIKVISION, Pelco-P, Pelco-D protocol

# DS-2AE4023(N)I-D 700TVL IR Analog PTZ Dome Camera



<b>General</b>	
Menu Language	English
Power	12VDC, Max.18W
Working Temperature / Humidity	-30 °C-65°C(-22°F-149°F) 90% or less
Protection Level	IP66 standard TVS 4,000V lightning protection, surge protection and voltage transient protection
Mounting	Various mounting modes optional
Dimensions	Φ164.5(mm)×295(mm)
Weight (approx.)	2Kg (4.41lbs)
Mount Option (only suitable for outdoor dome)	Long-arm wall mount: DS-1602ZJ; Corner mount: DS-1602ZJ-corner; Pole Mount: DS-1602ZJ-pole; Power box mount:DS-1602ZJ-box; Swan-neck mount: DS-1619ZJ

## Dimensions



## Accessories



DS-1602ZJ  
Wall Mount



DS-1602ZJ-Conner  
Conner Mount



DS-1602ZJ-Pole  
Pole Mount



DS-1602ZJ-Box  
Box Mount



DS-1663ZJ  
Ceiling mount



DS-1661ZJ  
Pendant mount



DS-1662ZJ  
Pendant mount



DS-1618ZJ  
Short arm wall  
Mount



DS-1005KI  
USB Joy-stick